

ABB-Welcome Access control  
Outdoor video station 3gang with keypad module  
front plate stainless steel, surface is brushed



Front plate made of 3 mm stainless steel.  
Video camera with automatic day/night switchover and infrared LEDs to illuminate the night shots.  
Communication unit and key module are backlit.  
Stamped labelling foil is enclosed.  
Mounting tool is enclosed.  
For flush-mounted installation with 83403 U-681-500/-689-500.  
For surface-mounted installation with 83403 AP-681-500/-689-500.  
Vertical/horizontal detection angle: 86°/67°  
Setting angle horizontal/vertical: +/-15°, mechanically adjustable  
Enables the opening of the door using a numerical code.  
256 users can be taught in.  
The keypad can also be used for the direct selection of the ABB-Welcome indoor stations.  
Programming directly on the module or using a web browser (requires IP gateway 83342).  
Consumer units: 10

Protection class (Device): IP 44, Temperature range (Device): -25 °C to 55 °C,  
Dimensions: (L x W x D): 349 mm x 135 mm x 43 mm,  
Not suitable for use with the camera interface (83327) nor camera module 180° (83503)., Additional information about commissioning and operation is contained in the system manual and the online operating manual of the current Online-Catalogue.

Order Code : 2CKA008300A0440  
Article No. : 83122/71/3-660-500  
EAN: 4011395199213