

Product Card

Room temperature controller extension unit with control function 6gang, studio white, ABB Tenton®



Room thermostat KNX

Room temperature controller extension unit with control function 6gang, studio white, ABB Tenton®



Type: SBS/U6.0.1-84

GTIN: 4011395255087

IP20

Freely configurable multifunction control element. Room temperature control/Controller extension with max. 6gang control With labelling field. Transparent labelling sheet with standard symbols included in delivery. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. Rocker switch left/right (switching/dimming/blind/value sender/light scenes/fan function). With integrated temperature sensor. With actual value temperature display With display of set-value temperature. The bus can be connected via enclosed terminal block. With integrated KNX bus coupler. Number of bus subscribers: 1

Technical specification

General Information

Product ID: 2CKA006330A0002

Packing

Package: 1

ETIM Data

Bus system KNX: Yes

© ABB 2023

Business ID 0763403-0

www.installationmaterials.com

Customer service

puh. +358 10 222 1999

contact.center@fi.abb.com

ABB Exchange

+358 10 22 11

Product Card

Room temperature controller extension unit with control function 6gang, studio white,



ABB Tenton®

Bus system KNX radio:	No
Bus system radio frequent:	No
Bus system LON:	No
Bus system Powernet:	No
Other bus systems:	None
Radio frequent bidirectional:	No
Assembly arrangement:	Control element
Mounting method:	Flush mounted (plaster)
With local operation:	No
With anti-theft/dismantling protection:	Yes
With LED indication:	Yes
With display:	Yes
Material:	Plastic
Material quality:	Thermoplastic
Surface protection:	Untreated
Surface finishing:	Glossy
Colour:	White
RAL-number (similar):	9016
Transparent:	No
External sensor:	No
Manual set point setting:	Yes
Presence button:	Yes
Parallel-service possible:	Yes
Degree of protection (IP):	IP20
With bus connection:	No
Min. depth of built-in installation box:	30.7 mm